



INSTITUT NATIONAL DE RECHERCHE EN INFORMATIQUE ET EN AUTOMATIQUE

Project-Team hipercom

High PERformance COMmunication

Paris - Rocquencourt

THEME COM

Activity
R *eport*

2007

Table of contents

1. Team	1
2. Overall Objectives	1
3. Scientific Foundations	2
3.1. Analytical information theory	2
3.2. Methodology of telecommunication algorithm evaluation	2
3.3. Network traffic and architecture models	3
3.4. Algorithm conception and implementation	4
4. Application Domains	4
4.1. Wireless mobile ad hoc networks	4
4.2. Services over mobile networks	5
4.3. Community Network	5
5. Software	5
6. New Results	6
6.1. Massive mobile dense wireless networks	6
6.1.1. Executive summary	6
6.1.2. Scientific achievements	7
6.1.2.1. Scaling and spatial capacity in non uniform wireless networks	7
6.1.2.2. Time capacity and node mobility	7
6.1.2.3. Overhead reduction in large networks	8
6.1.2.4. Opportunistic routing	8
6.1.2.5. Intermittent and delay tolerant networks	8
6.1.3. Collaborations	8
6.2. New services and protocols	8
6.2.1. Executive summary	8
6.2.2. Scientific achievements	10
6.2.2.1. Optimized Link State Routing (OLSR)	10
6.2.2.2. Bandwidth reservation in mobile ad hoc networks	10
6.2.2.3. Routing based on packet delay distribution in multihop ad hoc network	10
6.2.2.4. Multicast services in mobile ad hoc networks	10
6.2.2.5. Network coding	10
6.2.2.6. Autoconfiguration	11
6.2.2.7. Security in OLSR	11
6.2.2.8. Cross layer, sensor networks, energy efficiency	11
6.2.3. Collaborations	12
6.3. Integration wireless and backbone	12
6.3.1. Executive summary	12
6.3.2. Scientific achievements	13
6.3.2.1. Optimized Database exchange and check	13
6.3.2.2. OSPF-MPR	13
6.3.2.3. Gateway OSPF/OLSR	13
6.3.3. Collaboration	13
7. Contracts and Grants with Industry	13
7.1. COM2REACT	13
7.2. CELAR	14
7.3. OCARI	14
7.4. SARA	15
7.5. RAF	15
7.6. MOBISIC	15
7.7. EXPESHARE	15

8. Dissemination	16
8.1. University teaching	16
8.2. Participation to workshops, invitations	16
8.3. Standardization	17
8.4. Associated teams and other international projects	18
9. Bibliography	18

1. Team

Head of project-team

Philippe Jacquet [Ingénieur Général en Chef des Mines(DR), HdR]

Vice-head of project-team

Pascale Minet [Research Associate (CR), HdR]

Administrative assistant

Danielle Croisy [shared time (with Gang)]

Research scientists

Cédric Adjih [Research Associate (CR)]

Emmanuel Baccelli [Research Associate Futurs(CR)]

Paul Mühlethaler [Ingénieur en Chef de l'Armement (DR), HdR]

Khaldoun Alagha [LRI (Paris XI), HdR]

Anis Laouiti [INT (Evry)]

Thomas Clausen [Assistant Professor(Polytechnique)]

Ph D student

Song-Yean Cho [INRIA PhD]

Saoucène Mahfoudh [INRIA PhD]

Georges Rodolakis [Macquarie Univ Postdoc]

Yasser Toor [INRIA PhD]

Engineers

Farid Sayah [Engineer]

Short Term trainees

Rajesh Kumar [Avril-October 2007]

Manel Bourguiba [August 2007(ENSI)]

Sahla Masmoudi [August 2007(ENSI)]

Inès Korbi [December 2007(ENSI)]

Skander Azzaz [December 2007(ENSI)]

Short Term Visitors

Bernard Mans [Macquarie Univ (Australia)]

Leila Saidane [ENSI (Tunisia)]

Wojciech Szpankowski [Purdue University (USA)]

Nikita Vvedenskaya [IITP (Russia)]

2. Overall Objectives

2.1. Overall Objectives

Hipercom project-team aims to design, evaluate and optimize the telecommunication algorithms. The aimed areas are protocols, new telecommunication standards and quality of service management in networks. The aimed activity fields are centered around the new networks and services supporting internet. Although we address the whole spectrum of telecommunication domain, practically the Hipercom project team is specialized in local area networking, local loops, in particular mobile ad hoc networking. However the thematic extends to the information theory and modelization of internet graph and traffics.

The scientific foundations are the following:

- Analytic information theory,
- Methodology for telecommunication algorithm evaluation,
- Traffic and network architectures evaluation,
- Algorithms conception and implementation

The objectives assigned to HIPERCOM were:

- Massive mobile dense wireless networks
- New services and protocols
- Wireless and backbone integration
- Convergence 4G manet internet

The last objective about the convergence between 4G and manet has been put aside to the benefit of the three other objectives. The main reason is because there is no real demand in this very technological item.

3. Scientific Foundations

3.1. Analytical information theory

Keywords: *channel capacity, compression, predictors.*

Participants: Philippe Jacquet, Wojciech Szpankowski.

Information theory Branch of mathematics dedicated to the quantification of the performance of a medium to carry information. Initiated by Shannon in 1948.

Abstract. Information theory and analytical methods play a central role in the networking technology. It identifies the key parameter that must be quantified in order to characterize the performance of a network.

The analytical information theory is part of the foundations of the Hipercom project. This is a tool box that has been collected and adapted from the areas of the analysis of algorithms and the information theory. It provides powerful tool for the analysis of telecommunication algorithms. The analysis of the behavior of such algorithms in their asymptotic range are fundamental in order to identify their critical parts. It helps to design and properly scale the protocols. Application of analytical information theory ranges from channel capacity computations, compression algorithm performance evaluation, predictor designs.

3.2. Methodology of telecommunication algorithm evaluation

Keywords: *deterministic performance, probabilistic performance.*

Participants: Cédric Adjih, Emmanuel Baccelli, Thomas Clausen, Philippe Jacquet, Paul Muhlethaler, Saoucene Mahfoudh, Pascale Minet, Farid Sayah, Yasser Toor.

Abstract. We develop our performance evaluation tools towards deterministic performance and probabilistic performance. Our tools range from mathematical analysis to simulation and real life experiment of telecommunication algorithms.

One cannot design good algorithms without good evaluation models. Hipercom project team has an historically strong experience in performance evaluation of telecommunication systems, notably when they have multiple access media. We consider two main methodologies:

- Deterministic performance analysis,
- Probabilistic performance analysis

In the deterministic analysis, the evaluation consists to identify and quantify the worst case scenario for an algorithm in a given context. For example to evaluate an end-to-end delay. Mathematically it consists into handling a $(\max,+)$ algebra. Since such algebra is not commutative, the complexity of the evaluation of an end-to-end delay frequently grows exponentially with the number of constraints. Therefore the main issue in the deterministic evaluation of performance is to find bounds easier to compute in order to have practical results in realistic situations.

In the probabilistic analysis of performance, one evaluate the behavior of an algorithm under a set of parameters that follows a stochastic model. For example traffic may be randomly generated, nodes may move randomly on a map. The pioneer works in this area come from Knuth (1973) who has systemized this branch. In the domain of telecommunication, the domain has started a significant rise with the appearance of the problematic of collision resolution in a multiple access medium. With the rise of wireless communication, new interesting problems have been investigated.

The analysis of algorithm can rely on analytical methology which provides the better insight but is practical in very simplistic models. Simulation tools can be used to refine results in more complicated models. At the end of the line, we proceed with real life experiments. To simplify, experiments check the algorithms with 10 nodes in maximum, simulations with 100 nodes maximum, analytical tools with more 1,000 nodes, so that the full range of applicability of the algorithms is investigated.

3.3. Network traffic and architecture models

Keywords: *dynamic nodes, mobility models, network topologies, traffic source models.*

Participants: Cédric Adjih, Philippe Jacquet, Georges Rodolakis.

Power laws probability distributions that decays has inverse power of the variable for large values of the variable. Power laws are frequent in economic and statistical analysis (see Pareto law). Simple models such as Poisson processes and finite state Markov processes don't generate distributions with power laws.

Abstract. Network models are important. We consider four model problems: topology, mobility, dynamics and traffic models.

One needs good and realistic models of communication scenarios in order to provide pertinent performance evaluation of protocols. The models must assess the following key points:

- The architecture and topology: the way the nodes are structured within the network
- The mobility: the way the nodes move
- The dynamics: the way the nodes change status
- The traffic: the way the nodes communicate

For the architecture there are several scales. At the internet scale it is important to identify the patterns which dictate the node arrangement. For example the internet topology involves many power law distribution in node degree, link capacities, round trip delays. These parameters have a strong impact in the performance of the global network. At a smaller scale there is also the question how the nodes are connected in a wireless network. There is a significant difference between indoor and outdoor networks. The two kinds of networks differ on wave propagation. In indoor networks, the obstacles such as walls, furniture, etc, are the main source of signal attenuations. In outdoor networks the main source of signal attenuation is the distance to the emitter. This lead to very different models which vary between the random graph model for indoor networks to the unit graph model for outdoor networks.

The mobility model is very important for wireless network. The way nodes move may impact the performance of the network. For example it determines when the network splits in distinct connected components or when these components merge. With random graph models, the mobility model can be limited to the definition of a link status holding time. With unit disk model the mobility model will be defined according to random speed and direction during random times or random distances. There are some minor complications on the border of the map.

The node dynamic addresses the elements that change inside the node. For example its autonomy, its bandwidth requirement, the status of server, client, etc. Pair to pair networks involve a large class of user that frequently change status. In a mobile ad hoc network, nodes may change status just by entering a coverage area, or because some other nodes leaves the coverage area.

The traffic model is very most important. There are plenty literature about traffic models which arose when Poisson models was shown not to be accurate for real traffics, on web or on local area networks. Natural traffic shows long range dependences that don't exist in Poisson traffic. There are still strong issues about the origin of this long range dependences which are debated, however they have a great impact on network performance since congestions are more frequent. The origin are either from the distribution of file sizes exchanged over the net, or from the protocols used to exchange them. One way to model the various size is to consider on/off sources. Every time a node is on it transfers a file of various size. The TCP protocol has also an impact since it keeps a memory on the network traffic. One way to describe it is to use an on/off model (a source sending packets in transmission windows) and to look at the superposition of these on/off sources.

3.4. Algorithm conception and implementation

Keywords: *Access protocols, QoS, routing, scheduling.*

Participants: Cédric Adjih, Emmanuel Baccelli, Thomas Clausen, Philippe Jacquet, Paul Muhlethaler, Saoucene Mahfoudh, Pascale Minet, Farid Sayah, Yasser Toor.

Abstract. Algorithms are conceived with focal point on performance. The algorithms we specify in detail range between medium access control to admission control and quality of service management.

The conception of algorithms is an important focus of the project team. We specify algorithms in the perspective of achieving the best performance for communication. We also strive to embed those algorithms in protocols that involve the most legacy from existing technologies (Operating systems, internet, Wifi). Our aim with this respect is to allow code implementations for real life experiment or imbedded simulation with existing network simulators. The algorithm specified by the project ranges from multiple access schemes, wireless ad hoc routing, mobile multicast management, Quality of service and admission controls. In any of these cases the design emphasize the notions of performance, robustness and flexibility. For example, a flooding technique in mobile ad hoc network should be performing such to save bandwidth but should not stick too much close to optimal in order to be more reactive to frequent topology changes. Some telecommunication problems have NP hard optimal solution, and an implementable algorithm should be portable on very low power processing unit (e.g. sensors). Compromise are found are quantified with respect to the optimal solution.

4. Application Domains

4.1. Wireless mobile ad hoc networks

Keywords: *Community Networks, Services over mobile networks, Wireless mobile ad hoc networks.*

Abstract. Mobile wireless network have numerous application in rescue and emergency operation, military tactical networking and in wireless high speed access to the internet.

A mobile ad hoc network is a network made of a collection of mobile nodes that gather spontaneously and communicate without requiring a pre-existing infrastructure. Of course a mobile ad hoc network use a wireless communication medium. They can be applied in various contexts:

- military;
- rescue and emergency;
- high speed access to internet.

The military context is the most obvious application of mobile ad hoc networks.

Soldiers invading a country won't subscribe in advance to the local operator. On the reverse side, home units won't use their local operators firstly because they will likely be disrupted in the first hours of the conflict, and secondly because a wireless communication via an operator is not stealth enough to protect the data and the units. In Chechny, a general has been killed by a missile tracking the uplink signal of his portable phone.

The rescue context is halfway between military and civilian applications. In the september 11 disaster, most of the phone base station of the area have knocked out in less than twenty minutes. The remaining base stations were unable to operate because they could not work in ad hoc mode. The Wireless Emergency Rescue Team recommended afterward that telecom operators should provide ad hoc mode for their infrastructure in order to operate in emergency situation in plain cooperation with police, firemen and hospital networks.

Mobile ad hoc network provide an enhanced coverage for high speed wireless access to the internet. The now very popular WLAN standard, WiFi, provides much larger capacity than mobile operator networks. Using a mobile ad hoc network around hot spots will offer high speed access to much larger community, including cars, busses, trains and pedestrians.

4.2. Services over mobile networks

Abstract. New wireless network calls for new services that fullfil the requirement in terms of mobility and capacity.

The generalization of a new generation of mobile networks calls for a new set of services and applications. For example:

- Indoor and outdoor positioning
- Service discovery and localisation
- Multicast and quality of services

Quality of service has become the central requirement that users expect from a network. High throughput, service continuity are critical issue for multimedia application over the wireless internet where the bandwidth is more scarce than in the wired world. A significant issue in the ad-hoc domain is that of the integrity of the network itself. Routing protocols allow, according to their specifications, any node to participate in the network - the assumption being that all nodes are behaving well and welcome. If that assumption fails - then the network may be subject to malicious nodes, and the integrity of the network fails. An important security service over mobile networks is to ensure that the integrity of the network is preserved even when attacks are launched against the integrity of the network.

4.3. Community Network

Abstract. There is an increasing demand to deploy network within a community, rural or urban, with cabled or wireless access.

Community networks or citizen network are now frequent in big cities. In America most of the main cities have a community network. A community network is using the communication resource of each member (ADSL, Cable and wireless) to provide a general coverage of a city. Pedestrian in the street or in city mails can communicate via a high speed mobile mesh network. This new trend now appears in Europe with many experiments of the OLSR routing protocol in Paris, Lille, Toulouse, Berlin, Bruxelles, Seattle. The management of such networks is completely distributed and makes them very robust to faults. There is room for smart operators in this business.

5. Software

5.1. OLSR softwares

Keywords: *Internet protocol, routing protocol.*

Participants: Cédric Adjih [correspondant], Emmanuel Baccelli, Thomas Clausen, Philippe Jacquet, Paul Muhlethaler, Saoucene Mahfoudh, Pascale Minet, Farid Sayah, Yasser Toor.

Abstract. The routing protocol OLSR has been implemented in Linux and Windows for real experiment with Wireless LAN networks. There are also implementations for simulator such as NS-2 and Opnet.

The current version of OLSR, called OOLSR (for Object oriented OLSR), is IETF RFC compliant with multiple interfaces and tunable mobility parameters and has been fully tested during the three successive OLSR Interops in San Diego, August 2004, Paris August 2005 and Tokyo/Niigata 2006. This version runs with Linux and Windows. The linux daemon is very easy to install and can be downloaded from the web page. There have been more than 6000 downloads of the code which is exceptional for a routing protocol. This version also contains feature adaptable to wireless driver, such as the signal power monitor.

Related to OLSR, we have implemented and successfully tested in linux the Multicast routing protocol SMOLSR (Simple Multicast on OLSR) that efficiently broadcast data on wireless networks using MultiPoint Relays and the MOLSR (Multicast over OLSR) protocol. We have also implemented the MOST protocol (Multicast Overlay Spanning Trees) that forwards data to multicast group members on an overlay tree built on an OLSR shortest path tree.

Numerous code (including one in Python) have been developed for experiment and simulation (NS-2, Opnet). See <http://hipercom.inria.fr/olsr/>.

Other modules have been added to OOLSR dealing with autoconfiguration, security and QoS. Some of these modules have been experimented on the CELAR platform consisting of 18 nodes.

The code development of the next version of OLSR (OLSRv2) is under progress both at INRIA ROCQUEN-COURT and at POLYTECHNIQUE.

Hipercom has one ongoing ODL (operation de developpement logiciel): the goal is the extension and valorization of two protocols which have been developed as prototypes: multicast and quality of service protocols, for ad-hoc networks, based on OLSR (MOST and QOST).

6. New Results

6.1. Massive mobile dense wireless networks

Keywords: *Scaling properties, analytical models, routing protocols, transport capacity.*

Participants: Cédric Adjih, Emmanuel Baccelli, Song Yean Cho, Philippe Jacquet, Saoucene Mahfoudh, Pascale Minet, Paul Muhlethaler, Georges Rodolakis, Yasser Toor.

6.1.1. Executive summary

Scaling properties of mobile ad hoc network lead to an increase of global capacity when the network density increases or when the packets can be stored for a while in mobile nodes instead of being immediately retransmitted.

Gupta and Kumar have shown in 2000 that the transport capacity per node in a multihop ad hoc network decreases in $\frac{1}{\sqrt{N \log N}}$, N being the number of nodes in the network. Therefore the global capacity of the network increases in $\frac{\sqrt{N}}{\sqrt{\log N}}$. This is a surprising result since in wired network a collection of nodes connected to a single communication resource has a transport capacity that just remains constant (*i.e.* the average per node capacity decreases in $\frac{1}{N}$).

Therefore adding space to a multihop wireless network increases the capacity: this is the space capacity paradox.

When nodes randomly move, it turns to be more advantageous to store packets for a while on mobile routers instead of forwarding them immediately like hot potatoes. When the mobile router moves closer to the destination, then it can deliver packets on a much smaller number of hops. Of course the delivery delay is much longer, but the network capacity also increases by slowing non urgent packets. This is the time capacity paradox: by slowing packets, nodes mobility increases network capacity. This was hinted the first time by Grossglauser and Tse in 2002.

The great challenge is to find the good protocol and tunings that allow to adjust the delivery delay from zero to infinity in order to get a continuous increase in capacity. The challenge is two-sided: one has to keep the delivery delay between reasonable bounds and one has to consider realistic mobility models.

Existing protocols for Mobile Ad Hoc Networks (MANET) are highly efficient in routing data between mobile nodes that belong to the same connected component (cf. the protocols which have received the RFC status by the manet group of IETF). What about a disconnected network where source and destination may be located in two different connected components? In this case usual routing protocols drop packet due to host unreachable as no end-to-end route exists at that time.

A simple idea is to allow the router that has no available route to the destination to keep the packet in buffer until the conditions become more appropriate for forwarding. The forwarding conditions will change because of mobility: the router can move closer to the destination so that they belong to the same connected component and the packet can be delivered.

Indeed, the network may be continuously partitioned due to high mobility, and the traditional approach to allow a mobile node to wait for the network to be fully connected (i.e. form a unique component) or to wait to be in range of the destination may lead to unacceptable delays. Furthermore, concrete applications, such as Defence and Disaster-Relief, cannot always rely on such assumptions.

Nevertheless, even if the communicating nodes may never be within the same connected component, it is important to observe that a “communication path” may be available through time using intermediate nodes that are temporarily within reach of each other while moving, hence making such networks viable for critical applications. Depending on the nature of the environment, these networks are now commonly referred as Intermittently Connected MANET and Delay Tolerant Networks.

In between stands the problem of the fully connected network that forms a single connected component, but for which maintaining full knowledge of the topology would simply make the network collapse under its huge control traffic. In fact this is the main problem that wireless network engineering has to face, in most experiments the generation of control traffic is the main source of disruption.

6.1.2. Scientific achievements

6.1.2.1. Scaling and spatial capacity in non uniform wireless networks

We found a more precise instance of Gupta- Kumar result by using a simple but realistic network model based on slotted ALOHA with Poisson traffic. It turns out that when the traffic density increases then the average node neighborhood area shrinks so that the average encircled traffic load remains constant with an analytical expression..

In their original model Gupta and Kumar assume that the traffic density is constant, which is far from realistic. However we have derived similar generalized results when the traffic density is not uniform. In this case, the heavier is the local traffic, the smaller are the local neighborhood and the larger is the number of hops needed to cross the congested region. Therefore the shortest paths (in hop number as computed by OLSR) will have a natural tendency to avoid congested area. The path tend to follow trajectory that have analogy in non linear optic with variable indices.

6.1.2.2. Time capacity and node mobility

We have defined a protocol [ref mwc and itw] that takes advantage of node mobility in a general way. In short the packet stay with its host router as long as the latter does not evade too fast from its next hop (computed via a shortest path protocol such as OLSR). In the way we understand “too fast” stands the tuning parameters we discussed above. There is no need to have node geographical location and to physically measure motion vector, since everything can be done via the analysis of the dynamic of neighborhood intersections. We analytically derived performance evaluation under random walk mobility models. We plan to simulate the protocol in a real mobility scenario. This algorithm has application in Intelligent Transport System.

6.1.2.3. *Overhead reduction in large networks*

The first limitation of multihop wireless network is the size of the overhead per node that increases linearly with the size of the network. This is a huge improvement compared to classic internet protocols which have quadratic overhead increases. Nevertheless this still limit the network size to some thousands. We have analyzed the performance of OLSR with Fisheye feature that significantly reduce the overhead with respect to distance. In theory the overhead reduction allows to network size of several order of magnitude. Anyhow the tuning of the overhead attenuation with distance must be carefully done when the network is mobile, in order to avoid tracking failure. We showed that an overhead reduction within square root of the network size achieve this goal.

An alternative way to overhead reduction is ad hoc hierarchical routing and Distributed Hashing Table. Work has just begun in this area.

6.1.2.4. *Opportunistic routing*

The model of wireless networks based on dynamic graph does not well assess the real processes in a wireless network. In particular the range of transmission can greatly vary between packets, the graph keeping only the average range. Opportunistic routing consists into taking advantage of temporary extension of the transmission range in order to gain several hops. We have just started to work on a broadcast and unicast packet algorithms.

6.1.2.5. *Intermittent and delay tolerant networks*

We consider the problem of routing in these networks, with the sole assumption that the speed of the node mobility is less than the speed of transmitting a packet to a neighbour. We compare this problem with sound propagation in liquid. We show that various pattern of mobility and network clustering can be described by a single parameter such as the information speed propagation.

We introduce new algorithms that route a packet toward a remote destination. The different algorithms vary depending on the buffering and the capacity capabilities of the network (i.e. if one or more copies of a packet can be sent and/or be kept). All algorithms are based on link aging rumors across connected components. The packet bounces from connected components to connected components, thanks to node mobility. We establish several analytical properties using an analogy with the sound propagation in liquid where molecules creates temporary connected components where sounds travel very fast.

6.1.3. *Collaborations*

- Professor Bernard Mans, Macquarrie University, Sydney, Australia,
- TREC INRIA team,

6.2. **New services and protocols**

Participants: Cédric Adjih, Emmanuel Baccelli, Song Yean Cho, Philippe Jacquet, Saoucene Mahfoudh, Pascale Minet, Paul Muhlethaler, Georges Rodolakis, Farid Sayah, Yasser Toor.

6.2.1. *Executive summary*

The user of a mobile network very quickly experience problems with quality of service: links fade, connectivity disrupts, delays accumulate.

In a wireless network, the set of neighbors which with one node can communicate depends on transmission range, and numerous factors, and in addition the transmission range is often lower than the interference range (the range within which a node prevents correct transmissions of other nodes). Thus bandwidth reservation, a crucial step of quality of service, is an important and difficult problem.

The services and protocols that need careful adaptation are

- Connectivity continuity
- Bandwidth reservation
- Delay routing
- Connectivity control
- Autoconfiguration
- Security
- Energy efficiency

The connectivity continuity is the most important problem. Trivial in the wired world where a link failure is a rare event, it becomes problematic in the mobile world where link failure caused by mobility are frequent and normal. The first experiments of mobile ad hoc networks with regular internet protocols miserably failed simply because either the protocol was too slow to recover link failure, or when tuned appropriately was generating such a huge overhead that the network collapsed under its own weight. A new generation of routing protocols has arisen that allow a suitable control of connectivity in mobile networks. Among them the *Optimized Link State Routing* combines the optimization of overhead for mobile networks and the full internet legacy. It naturally provides path redundancy which accelerates link failure recovery.

The most important lesson that must be retained is that most of these optimizations become NP complete, which is a significant complication compared to their counterpart in the classical wired world. The reason for the NP-completeness is two-sided: on one side the co-interferences make impossible an optimization link by link, on the other side, the large dispersion of performance measurement makes simple heuristics ineffective. As an example, routing with respect to shortest delay average does not guarantee smallest probability of high delay.

Since the bandwidth is scarce, any multimedia application such as video streaming is resource demanding. For example a TV broadcast that uses a mesh network will rapidly exhaust the bandwidth if all connections are point to point. In this case multicast protocols that allow to gather all these point to point connections in a single flow is a need.

There are two classes of multicast protocols: the tree based protocols and the network coding protocols. In the first class the protocols take advantage of the relatively small size of the recipient node set. One can show equivalent results of Gupta and Kumar scaling properties but in the multicast plan when the ratio of recipient versus network size is a fundamental parameter. When this ratio tends to one the performance naturally worsens.

When the recipient set is the whole network, one can apply the network coding scheme with random packet combination. In network coding the packets are no longer isolated: relay nodes make linear combination of packets and transmit mixed packets. In theory the performance of network coding is better than isolated packet multicast. In practice network coding is simpler to operate does not need topology management such as spanning trees or Connected Dominating Set. The reason for this is highly non intuitive, as if packet superposition was acting like state superposition in quantum mechanics, leading to non expected results.

Quality of service has become the central requirement that users expect from a network. High throughput, service continuity are critical issues for multimedia applications over the wireless internet where the bandwidth is more scarce than in the wired world. A significant issue in the ad-hoc domain is that of the integrity of the network itself. Routing protocols allow, according to their specifications, any node to participate in the network - the assumption being that all nodes are behaving well and welcome. If that assumption fails - then the network may be subject to malicious nodes, and the integrity of the network fails. An important security service over mobile networks is to ensure that the integrity of the network is preserved even when attacks are launched against the integrity of the network.

6.2.2. Scientific achievements

6.2.2.1. Optimized Link State Routing (OLSR)

The routing protocol OLSR is universally known in the mobile wireless community (more than 475,000 hits on Google). It has numerous implementations and is used in many wireless networks. It is a proactive protocol with full internet legacy which is based on partial topology information exchange, that non the less provide optimal path with additive metrics (such as BGP/OSPF). It is an experimental RFC within IETF and soon will become a full standard under the name OLSRv2.

6.2.2.2. Bandwidth reservation in mobile ad hoc networks

We have shown that the search of a good path for a new connection that does not destroy the quality of service of existing connections is an NP-hard problem. The result is independent on how the bandwidth nodes interfere as long they interfere at least on one hop. In this area, one contribution was the definition and testing of an efficient reservation algorithm bandwidth reservation, respecting wireless network constraints. A second contribution is more accurate computation of remaining link bandwidth by considering bandwidth on other links multiplied by the average packet retransmission on this link (inverse of packet successful transmission rate).

We have also proposed a solution called QoS-OLSR that enhances OLSR with Quality of Service support. This solution, taking radio interferences into account, ensures that QoS flows, if accepted by the admission control, will receive a bandwidth close to this requested. This solution has been implemented on the MANET/OLSR demonstrator of CELAR (MoD).

6.2.2.3. Routing based on packet delay distribution in multihop ad hoc network

Since propagation delays between routers are negligible, most delays occur in queueing and medium access control processing. Contrary to previous common belief there is no need of network synchronization. The objective is to proactively determine the delay in absence of packet data traffic. The estimate of delay distribution is done via analytical method. In order to keep control on quality of service flows we use source routing forwarding options.

6.2.2.4. Multicast services in mobile ad hoc networks

We have designed the Multicast extension for the Optimized Link State Routing protocol (MOLSR). MOLSR is in charge of building a multicast structure in order to route multicast traffic in an ad-hoc network. MOLSR is based on natural radio broadcast. This multicast protocol has also been implemented on the MANET/OLSR demonstrator of CELAR (MoD). A new version of the multicast protocol called MOST uses unicast traffic.

We have derived a theoretical upper bound of the multicast capacity in wireless network. This result is an extension of Gupta and Kumar result about unicast capacity in wireless network. It is shown that the multicast delivery allows an increase of capacity of the order of the square root of the size of the multicast group compared to the attainable capacity if only parallel unicast connections were used. We have also shown that the protocol MOST actually attains this upper bound.

6.2.2.5. Network coding

We have just started the work in this area. We have proven optimality of network coding in 1D and 2D dense network and have designed a practical protocol, DRAGONCAST, that fits these properties. We propose a simple protocol for network coding. We describe how the packets flowing from the one source evolves in *waves*, and by studying the propagation of the waves, we are able to quantify the performance of the simple protocol. We analyze the performance of the protocol in an unit graph wireless network model in an 1 dimension model, with an asymptotic model and show that it is asymptotically close to optimal flooding obtained via MPR flooding. In 2 dimension model, we conjecture similar performance, simulations show that the protocol outperforms the MPR flooding (which is no longer optimal).

The simple network coding protocol is interesting since it does not need sophisticated network management such as neighborhood management and two-hop monitoring as it is demanded with MPR flooding. Nevertheless the asymptotic performance are obtained with rather large dimensions, which lead to non negligible information extraction cost from rather large linear combinations.

6.2.2.6. Autoconfiguration

Thomas Clausen is co-chair of the IETF working group *Autoconfiguration in MANET*.

A preconditioning for all routing protocols, OLSR included, is that each node is identifiable through an unique identifier. We have developed, and published, a simple auto-configuration mechanism for OLSR networks, aiming at solving the simple but common problem of one or more nodes emerging in an existing network. Our solution is simple, allowing nodes to acquire an address in two steps: first, acquiring a locally unique address from a neighbor node. Then, with that locally unique address and using the neighbor from which the address was acquired as proxy, obtaining a globally unique address.

6.2.2.7. Security in OLSR

This issue is a hot issue in ad hoc networks since these networks are inherently open networks. We have reached the following results:

1. we have designed two security mechanisms to counter most of the attacks when we assume that there is no compromised nodes in the network; the first one has been implemented on the MANET/OLSR demonstrator of CELAR (MoD).
2. in presence of compromised nodes we have proposed mechanisms to detect compromised nodes or links and to remove such nodes or links in a numerous configurations of attacks.

6.2.2.8. Cross layer, sensor networks, energy efficiency

The diversity of the applications supported by wireless sensor networks explain the success of this type of network. These applications concern various domains as environmental monitoring, wildlife protection, emergency rescue, home monitoring, target tracking, exploration mission in hostile environments... Sensor nodes are characterized by a small size, a low cost, an advanced communication technology, but also a limited amount of energy. This energy can be very expensive, difficult or even impossible to renew. That is why, energy efficient strategies are required in such networks in order to maximize network lifetime. Solutions to maximize network lifetime can be classified into four categories:

- *Topology control*: These strategies adjust the transmission power of wireless nodes to spare energy;
- *Reduction of the volume of information transferred*: These strategies aggregate data with or without clustering, optimize network flooding, tune the periodicity of information refreshment;
- *Nodes activity scheduling*: as the sleeping state is the radio state consuming the least energy, these strategies make nodes sleep in order to spare energy, while ensuring network and application functions. Large benefits are expected.
- *Energy efficient routing*: Such strategies notice that a multihop transmission is energy consuming and reducing the energy spent in the transmission of a packet from its source to its destination would increase network lifetime. Moreover, avoiding nodes with a low residual energy would also contribute to prolong network lifetime. Avoiding nodes that already have a high traffic load would reduce medium access contention, collisions if the medium access type is CSMA-CA and then spare energy lost in useless transmissions.

For low cost device, OLSR must be reduced and integrated with medium access control and application. This cross layering is an important starting activity which allows experiments on large scale. We have shown how to extend the standardized OLSR routing protocol, in order to make it energy efficient. We have first defined an energy model for multihop transmissions. The energy cost of a one-hop transmission is evaluated, taking into account the energy lost in transmitting, receiving, overhearing and interferences. We have then evaluated the energy cost of multihop transmissions. Because of radio interferences, the selection of a unicast path, between a source and a destination, ensuring that each node has sufficient residual energy is NP-hard. The OLSR extension we propose, called *OLSRE*, selects the path minimizing the energy consumed in the end-to-end transmission of a flow packet and avoids nodes with low residual energy. An extensive performance evaluation allows us to conclude that *OLSRE* maximizes both network lifetime and the amount of data delivered.

In wireless ad hoc and sensor networks, an analysis of the node energy consumption distribution shows that the largest part is due to the time spent in the idle state. This result is at the origin of SERENA, an algorithm to SchEDule RoutEr Nodes Activity. SERENA allows router nodes to sleep, while ensuring end-to-end communication in the wireless network. It is a localized and decentralized algorithm assigning time slots to nodes. Any node stays awake only during its slots and the slots assigned to its neighbors, it sleeps the remaining time. SERENA is based on distributed and localized two-hop coloring. The node's color is then mapped in time slot. Thus, each node is ensured to get at least one time slot, it also gets additional time slots proportionally to its traffic rate. Such a solution adapts to varying traffic rates and supports late node arrivals. The first benefit of SERENA is that less energy is lost in the idle state. Indeed, if a node has nothing to transmit and its neighbors are not transmitting, the node is sleeping. The second benefit is that SERENA contributes to significantly reduce the interference phenomenon that becomes negligible. Hence, SERENA considerably improves the energy efficiency of wireless ad hoc and sensor networks.

6.2.3. Collaborations

- Many contractual collaborations:
 - MoD (QoS, security, interconnection between the OLSR and OSPF routing domains),
 - Hitachi (Vehicular applications, OLSRv2),
 - OCARI project (QoS, cross layer, energy efficiency),
 - SARAH project (QoS, localization),
 - Com2react (vehicular applications, multicast),
 - STIC INRIA-Tunisian Universities: the team of Prof. Leila Saidane at ENSI (QoS and routing).
- Non contractual:
 - BAE (OLSRv2),
 - Freie Universitaet (sensor networks, DHT).

6.3. Integration wireless and backbone

Participants: Cédric Adjih, Emmanuel Baccelli, Thomas Clausen, Song Yean Cho, Philippe Jacquet, Saoucene Mahfoudh, Pascale Minet, Paul Muhlethaler, Georges Rodolakis, Farid Sayah, Yasser Toor.

6.3.1. Executive summary

We have the following vision: in the future mobile internet and static internet will have their core deeply intricated. This means that mobile ad hoc networks will be attached to the core network, form extension and even be part of it. For example in disaster area, a wireless network could replace the destroyed infrastructure and help to the emergency operations.

With this perspective items such as Autoconfiguration, Security are of crucial importance. However there is a potential conflict between a large population of fixed nodes based on ancient protocol and a smaller but more dynamic population based on new protocols. In the integration both population must cooperate in an hybrid protocol.

The difficulty is to build protocols that are as dynamic and efficient as MANET protocols but can support the legacy of the old and heavy internet protocols. The challenge is nevertheless achievable, because the dynamic part of the network needs less frequent updates from the fixed part of the network. Moreover the natural abundance of resource in the fixed part of the network allows it to support the more frequent updates from the mobile part.

OLSR has been found to be the natural best candidate for this challenge since it gathers dynamic and optimization with internet legacy.

6.3.2. Scientific achievements

6.3.2.1. Optimized Database exchange and check

The problem of unreliable broadcast and less frequent update is that a missing routing information can lead to lasting problems (loops, disconnections). We have specified an integrity check of distributed databases. We have replaced the heavy check done in wired world that exchanges database headers line by line by a collective check based on signature broadcast and exchange. That way the routing database are synchronized more quickly and discrepant part identified with a logarithmic cost instead of a cost linear to the database size.

6.3.2.2. OSPF-MPR

The INRIA proposal is based on OLSR, in particular the optimization feature called MultiPoint Relay. The overhead reduction is similarly based on flooding reduction, and topology reduction. In particular OSPF-MPR supports optimized routing based on general additive metrics as in OSPF and adapt its topology reduction to those metrics. Compared to OLSR, OSPF-MPR has a feature called adjacency reduction inherited from OSPF, using broadcasted acknowledgement that enhances routing database synchronization. This feature is also optimized with MPR.

6.3.2.3. Gateway OSPF/OLSR

The MANET extension protocols being largely experimental, we have developed a software that enable a gateway between OSPF and OLSR and allows the convergence of both protocols on existing software. This software has been implemented on the MANET/OLSR demonstrator of CELAR (MoD).

6.3.3. Collaboration

We received support from MoD for this activity.

7. Contracts and Grants with Industry

7.1. COM2REACT

Participants: Cédric Adjih, Anis Laouiti, Paul Muhlethaler, Yasser Toor.

COM2REACT's overall objective is to establish the feasibility of an effective control of traffic geared to address both efficiency and safety. Its implementation will involve the deployment of two two-way communication systems: vehicle to vehicle (V2V), and vehicle to infrastructure (V2I). This structure will facilitate significant improvement in the flow of information acquired by moving vehicles and in its quality and reliability, thereby enhancing road efficiency and traffic safety on urban, intercity arterials and rural roads. A key objective of COM2REACT is the implementation of the middle control level by means of a virtual traffic control sub-centre, which manages a moving group of vehicles in close proximity. The virtual sub-centre (VSC) functions locally via the V2V communication system, it also transmits, by means of the V2I communication, selective data to an RCC (Regional Control Center) and receives, in return, instructions to distribute to the vehicles. The role of VSC is set, unnoticeable by the driver, to one of the vehicles in the group according to rules imbedded in all COM2REACT vehicles. The potential impact of the COM2REACT project consists of the developing advanced systems for vehicle cooperation that enhance both safety and information on European roads.

By proving the efficiency of such architecture, COM2REACT will contribute significantly to the introduction of V2V technologies. In COM2REACT, the V2V technology will be based on the *OLSR (Optimized Link State Routing)* protocol. This protocol is optimized for dense networks, this is particularly well suited for Vehicular Ad hoc NETWORKS (VANETs). Multipoint routing extension of OLSR e.g. MOLSR (Multicast OLSR) or SMOLSR (Simple Multicast OLSR) can be very useful in VANETs and should probably be used in COM2REACT. The COM2REACT project and VANETs are excellent examples of application for the OLSR technology.

7.2. CELAR

Participants: Cédric Adjih, Emmanuel Baccelli, Philippe Jacquet, Anis Laouiti, Pascale Minet, Paul Muhlethaler, Dang Nguyen.

The CELAR project has started in April 2004 for three years. Its aim is to enhance the demonstrator of mobile ad-hoc network MANET/OLSR, previously implemented with secured routing, quality of service (QoS), and an OLSR/OSPF gateway. This project is funded by CELAR (Centre d'Electronique de l'Armement, French MoD/DGA). This testbed allows CELAR to make demonstrations with a real mobile ad-hoc network, and evaluate the potential benefits of such a network in military tactical applications, with a special focus on performances and reliability. It is made up of 18 nodes: 10 OLSR routers and 8 terminals (VAIOs and iPAQs). Routers and terminals are equipped with 802.11b cards and measurements tools on Linux. They implement the OLSR routing protocol. Performance measurements have been done in various configurations including different traffic types, network topology and mobility (e.g., pedestrian and/or vehicle).

More precisely, this project addresses four topics :

- *secured routing*: in a mobile ad-hoc network, the use of secured tunnels is not sufficient to protect routing against potential attacks. First, we have analyzed potential attacks against OLSR routing and we have precised our security goal. In the attacks, we also consider the case of compromised nodes in the network. These nodes have a certain knowledge of the network secret keys. In the case where the network does not encompass compromised nodes, we have design a security architecture which can counter most of the identified attacks except the wormhole attack. This security architecture is base on timestamping and signing message. For the case where there is compromised nodes in the network we have proposed various scheme to mitigate the effects of attacks in such a situation.
- *QoS management*: it is more complex in mobile ad-hoc networks than in wired networks because of their high dynamicity, the presence of interferences and the limited resources. We propose an extension of OLSR conciliating both QoS support and optimized flooding. Flows having QoS requirements are source routed on the shortest path providing the requested bandwidth. Best effort flows are routed hop by hop and regulated by leaky buckets. Simulation results show that QoS flows receive a throughput close to this request and have a high delivery rate. Moreover, this extension supports node mobility : up to 20m/s with the default OLSR parameter values.
- *OLSR/OSPF gateway*: the aim is to allow exchanges of routing information between an OLSR network and an OSPF network. As both routing procols are link based, the OLSR/OSPF gateway will take advantage of this similarity.
- *up-to-date version of OLSR*: this CELAR testbed has been carried up on the OLSR version compliant with the RFC 3626.

The solution proposed for these four topics have been implemented on the testbed. Measurements made on this testbed are close to the simulations results. This MANET/OLSR testbed is frequently used in the exhibits organized by CELAR. It allows CELAR to demonstrate that MANET with OLSR routing are good candidates for tactical networks.

7.3. OCARI

Participants: Pascale Minet, Saoucene Mahfoudh.

The OCARI (Optimization of Ad hoc Communications in Industrial networks) project, funded by ANR, started in January 2007. It has a duration of 36 months. The industrial partners are EDF (coordinator), DCN and One-RF. The academic partners are LIMOS (Clermont Ferrand university), LATTIS (Toulouse university), LRI (Paris Sud university) and INRIA.

The OCARI project aims at developing and deploying a new generation of wireless sensor networks in industrial environments. It will propose adaptive networks taking into account highly constrained environments and allowing new applications to emerge. On the one hand, the OCARI infrastructure must meet the following constraints:

- a reduced energy consumption by means of protocols allowing nodes to sleep and an energy efficient routing,
- an environment with electromagnetic perturbations,
- a high versatility of the physical layer, limited network resources and energy constraints.

On the other hand, to meet the requirements of supported applications (remote command of actuators, tele-diagnostic...), new solutions will be brought to manage several communication modes, ranging from deterministic data transfers to delay tolerant transfers. A key issue is how to adapt routing algorithms to the industrial environment, taking into account more particularly limited network resources (e.g.; bandwidth), node mobility and hostile environment reducing radio range.

The INRIA contribution concerns energy efficient routing and nodes activity scheduling. The energy efficient extension of OLSR, called *OLSRE*, will be implemented on top of the MAC protocol defined by LATTIS and LIMOS. The MAC protocol is a variant of ZigBee ensuring some determinism and quality of service and allowing leave nodes (e.g. sensor, actuator) as well as router nodes to sleep. SERENA will be adapted to the specific context of OCARI (i.e.; very limited bandwidth 250kbps, small size messages 127 bytes, limited memory and limited processing power).

7.4. SARAH

Participants: Philippe Jacquet, Juan Antonio Cordero Fuertes.

The SARAH project, Service Ad hoc/Filaires: Developpement d'une Architecture de Reseau Integre, is an ANR project. It aims at developing an integrated architecture of network. It started in 2007. The partners are ALCATEL, FT R&D, LIP6, LRI, LSIIT, LSR-IMAG, SNCF, ENST, INRIA.

7.5. RAF

Participants: Paul Muhlethaler, Khaldoun Al Agha.

The RAF project, Réseaux ad hoc A Forte efficacité, belongs to the competitiveness cluster SYSTEM@TIC PARIS-REGION. It aims at designing self configuring ad hoc networks using reservation based access protocols using both time and frequency multiplexing. The project has three components : the study of ad hoc networks using a smart relaying function at the Phy/MAC level, the study and design of protocols for ad hoc networks solving simultaneously the access problem using reservation based techniques and the relaying issue for multi hop communication, the realization of a prototype using the IEEE 802.16e (WiMAX Mobile) technology.

The partners are Thalès, Alcatel Lucent, EADS, IEF, INRIA, LRI, Sagem DS, and Supelec.

7.6. MOBISIC

Participants: Philippe Jacquet, Emmanuel Baccelli.

The MOBISIC project belongs to the competitiveness cluster SYSTEM@TIC PARIS-REGION. It aims at designing and experimenting a modular system (Plug & Play), scalable adapted to events securing and local crisis management. The partners are THALES, ALCATEL, SAGEM, GEMALTO, BERTIN Technologies, EVITECH, SINOVA, SODERN, CEA, INRIA.

7.7. EXPESHARE

Participant: Philippe Jacquet.

The EXPESHARE project, EXPERIENCE SHARING in mobile peer communities, is an ITEA2 project. The aim is to allow virtual communities to exchange multimedia contents and experiences in a legal and secured way, using different types of personal assistants. The partners are Gemalto, INRIA, INT Evry, City Passenger, NXP Semiconductors, Evry university, Transatel, Brieftec, Capricode, CBT, Comverse, Engineering SpA, Innovalia, Kutalab, Nextel, Nokia, Philips, Shunra Software, SoftwareQuality Systems, Telefonica, University of Oulu, Paderborn university, Politecnica de valencia University, La Spenzia Roma university.

8. Dissemination

8.1. University teaching

Philippe Jacquet taught:

- in the MPRI MASTER(Paris) class : mobile ad hoc network/PeertoPeer networks (with Laurent Viennot),
- Ecole Polytechnique, Recitation Class : Foundation of computer science;
- at the EPITA school. Security in mobile and wireless networks;
- Master MISIC (Polytechnique) class: Telecommunication.

Pascale Minet taught:

- Networks and quality of service in Master "Systèmes Electroniques et Traitement de l'Information", at INSTN (Saclay).
- Mobile ad-hoc networks: medium access, routing and quality of service in Master "Informatique Fondamentale et Applications" of the university of Marne-la-Vallée.

Participation of Paul Muhlethaler to Lessons "Ad hoc Networks", The 802.11 Standard and wireless Network and for ENST B.

Thanks to the contacts created during the IETF meetings, we have started a fruitful close collaboration with Niigata University (prof. K. Mase) about mobile ad hoc networking. Common IETF drafts have been submitted. since buffer capacity might be limited on wireless routers.

Through common IETF activities with R. Wakikawa and K. Uehara, Hipercom has developed strong links with Keio University in Japan. This has recently been formalized through a "memo of understanding", between Hipercom and Keio University. Several joint academic publications as well as IETF publications have been the fruits of this collaboration on various subjects such as porting OLSR on BSD-ZEBRA, MANET-NEMO convergence, OLSR for IPv6.

This collaboration is also enabling Hipercom to take part in the WIDE consortium in Japan uniting Keio University (with J. Murai, the japanese Internet pioneer) and several industry heavy weights such as Hitachi, Mitsubishi, KDDI, NTT and other japanese universities and companies. This initiative is among other things organizing a large scale testing of OLSR on vehicles (with a prospect for testing OLSR on 1500 cars), which promises to be an extremely valuable experience for Hipercom, as no such scale study has been carried out to date.

Within the project STIC INRIA - Tunisian Universities entitled "Scheduling Techniques for Quality of Service Networks", Professor Leila Azouz Saidane from ENSI was invited by INRIA in July and December. Her four students Ines El Korbi, Manel Bourguiba, Sahla Masmoudi and Skander Azzaz came at INRIA for a training in August or December. Pascale Minet was invited by ENSI in April and November and Steven Martin in April too.

8.2. Participation to workshops, invitations

Philippe Jacquet was the PC chairman of the AofA conference, held in Juan-les-Pins, last June. This conference was organized by INRIA.

Philippe Jacquet belongs to the editorial board of the DMTCS journal.

Pascale Minet was reviewer of the PhD Thesis of Jian Li, "Garantir la qualité de service selon l'approche (m,k)-firm", Institut National Polytechnique de Lorraine, Nancy, February 2007.

She was president of the jury in the following PhD theses:

- Lamine Bougueroua, "Conception de systèmes temps réel déterministes en environnement incertain", University of Paris 12, Créteil, March 2007.
- Saddbouh Ould Cheikh El Medhi, "Un nouveau mécanisme de gestion de flu temps réel basé sur le paramètre échéance et son intégration dans Internet", University of Paris 13, Villetaneuse, June 2007.
- Hui Xue Zhao, "Analyse de faisabilité pour l'ordonnement de tâches en graphe dans les systèmes temps réel", University of Paris 12, Créteil, September 2007.

She was member of the program committee of:

- SPECTS'2007, 2007 International Symposium on Performance Evaluation of Computer and Telecommunication Systems, July 2007.
- Med-Hoc-Net'2007, 6th annual Mediterranean Ad-Hoc Networking conference, June 2007.
- SNPD'2007, 8th International Conference on Software Engineering, Artificial Intelligence, Networking and Parallel/Distributed Computing, July 2007.
- SAWN'2007, 3rd ACIS International Workshop on Self-Assembling Wireless Networks, July 2007.
- SERA'2007 (Int. Conf. on Software Engineering Research & Applications), August 2007.
- JDIR'2007, 8èmes Journées Doctorales en Informatique et Réseaux, January 2007.

Pascale Minet was reviewer for the following journals:

- IEEE/ACM Transactions on Networking,
- IEEE Transactions on Parallel and Distributed Systems, TPDS,
- Computer Networks Journal, COMNET,
- Simulation Modelling Practice and Theory journal,
- Annales des Télécommunications.

Paul Muhlethaler is an expert by the European Community for telecommunication projects.

Paul Muhlethaler was PhD Reviewer of Thierry Feuzeu Kwenkeu, "Extension de réseaux locaux Ethernet avec la commutation de label", University of Rennes, March 2007.

Emmanuel Baccelli received the Award for the best PhD Thesis at Polytechnique in 2007.

8.3. Standardization

The HIPERCOM project plays an important part in the standardization process. More precisely, it is active at:

- IETF in the following working groups:
 - AUTOCONF: T. Clausen is chairman;
 - MANET: see the numerous contributions of T. Clausen, P. Jacquet and C. Adjih;
 - OSPF: E. Baccelli is an important contributor;
 - NEMO: E. Baccelli takes an active part in this group.
- IEEE: HIPERCOM has pending patents with regard to 802.11;
- ETSI: Philippe Jacquet is the INRIA official contact;
- Car2Car: Paul Muhlethaler is the INRIA official contact;
- NATO: Pascale Minet made four presentations about OLSR and its extensions.

8.4. Associated teams and other international projects

The HIPERCOM project-team works with:

- University of Macquarie, Sidney, Australia: Prof. Bernard Mans: "Algorithmics for Extremely Mobile Wireless Networks",
- ENSI, Tunis, Tunisia: Prof. Leila Saidane: "Quality of service and performance evaluation of routing in MANETs".

9. Bibliography

Major publications by the team in recent years

- [1] C. ADJIH, L. GEORGIADIS, P. JACQUET, W. SZPANKOWSKI. *Is the internet fractal ?*, in "SODA 2002, San Francisco, USA", 2002.
- [2] C. ADJIH, P. JACQUET, N. VVEDENSKAYA. *Performance evaluation of a single queue under multi-user TCP connections*, Technical report, INRIA, March 2001, <http://hal.inria.fr/inria-00072484>.
- [3] T. CLAUSEN, P. JACQUET, A. LAOUITI, P. MUHLEHALER, P. MINET, A. QAYYUM, C. ADJIH, L. VIENNOT. *RFC 3626*, in "Optimized Link State Routing Protocol (OLSR), MANET working group", 2003.
- [4] L. GEORGE, S. KAMOUN, P. MINET. *First come first served: some results for real-time scheduling*, in "ISCA 14th int. conf. on Parallel and Distributed Computing System PDCS'2001, Dallas, Texas", August 2001.
- [5] L. GEORGE, D. MARINCA, P. MINET. *A solution for a deterministic QoS in multimedia systems*, in "International Journal on Computer and Information Science", vol. 1, n^o 3, October 2000, p. 106-119.
- [6] P. JACQUET. *11*, in "Traffic and queueing from an unbounded set of independent memoryless on/off sources", K. PARK, W. WILLINGER (editors), Wiley, 2000, p. 269-283.
- [7] P. JACQUET. *Elements de théorie analytique de l'information, modélisation et évaluation de performances*, mémoire d'habilitation, Ph. D. Thesis, Université de Versailles Saint-Quentin, juillet 1998.
- [8] P. JACQUET. *Long term dependences and heavy tails in traffics and queues generated by memoriless on/off sources in series*, Technical report, n^o RR-3516, INRIA, 1998, <http://hal.inria.fr/inria-00073168>.
- [9] P. JACQUET, V. JOLY. *Capacity of retro-information channels*, in "2000 IEEE International Symposium on Information Theory, Sorrento, Italie", June 2000, 182.
- [10] P. JACQUET, P. MINET, A. LAOUITI, L. VIENNOT, T. CLAUSEN, C. ADJIH. *Multicast Optimized Link State Routing*, Technical report, IETF, December 2001.
- [11] P. JACQUET, P. MINET, P. MUHLEHALER, N. RIVIERRE. *Data transfer for HIPERLAN*, in "Wireless Personal Communications", special issue on the HIgh PErformance Radio Local Area Network (HIPERLAN), vol. 1, n^o 4, January 1997.

- [12] P. JACQUET, P. MINET, P. MUHLETHALER, N. RIVIERRE. *Increasing reliability in cable-free radio LANs - low level forwarding in HIPERLAN*, in "Wireless Personal Communications", special issue on the High Performance Radio Local Area Network (HIPERLAN), vol. 1, n^o 4, January 1997.
- [13] P. JACQUET, P. MINET, P. MUHLETHALER, N. RIVIERRE. *Priority and collision detection with active signaling - the channel access mechanism of HIPERLAN*, in "Wireless Personal Communications", special issue on the High Performance Radio Local Area Network (HIPERLAN), vol. 1, n^o 4, January 1997.
- [14] P. JACQUET, W. SZPANKOWSKI. *Analytical depoissonization and its applications*, in "Theoretical Computer Science", vol. 201, n^o 1-2, 1998, p. 1–62.
- [15] P. JACQUET, W. SZPANKOWSKI. *Entropy calculation via analytic depoissonization*, in "IEEE Transaction on Information Theory", vol. 45, n^o 4, May 1999.
- [16] S. KAMOUN, P. MINET. *Periodic scheduling of distributed tasks with consistency and hard real-time constraints*, in "International journal of computer and information science", ed. International association for computer & information science, ACIS. ISSN 1525-9293, vol. 2, n^o 3, September 2001, p. 106-118.
- [17] A. LAOUITI, A. QAYYUM, L. VIENNOT. *Multipoint Relaying: An Efficient Technique for Flooding in Mobile Wireless Networks*, in "35th Annual Hawaii International Conference on System Sciences (HICSS'2001)", IEEE Computer Society, 2001.
- [18] P. MINET. *Temps réel, tolérance aux fautes et cohérence dans les systèmes distribués*, mémoire d'habilitation, Ph. D. Thesis, Université de Versailles Saint-Quentin, septembre 1998.
- [19] P. MUHLETHALER. *Contribution à la conception et à l'analyse d'algorithmes pour l'accès multiple et l'ordonnancement sous contraintes temporelles*, mémoire d'habilitation, Ph. D. Thesis, Université de Versailles Saint-Quentin, juillet 1998.
- [20] A. QAYYUM. *Analysis and evaluation of channel access schemes and routing protocols in wireless LANs*, Ph. D. Thesis, Université de Paris Sud, November 2000.
- [21] RES-10. *Radio Equipment and Systems (RES); High Performance Radio Local Area Network (HIPERLAN); Functional specification*, Technical report, ETSI, June 1996.
- [22] L. VIENNOT. *Complexity Results on Election of Multipoint Relays in Wireless Networks*, Technical report, n^o RR-3584, INRIA Rocquencourt, 1998, <http://hal.inria.fr/inria-00073097>.

Year Publications

Articles in refereed journals and book chapters

- [23] S. BOUDJIT, C. ADJIH, P. MUHLETHALER, A. LAOUITI. *Duplicate address detection and autoconfiguration in OLSR*, in "JUCS", vol. 13, n^o 1, 2007, p. 4-31.
- [24] P. JACQUET, G. SEROUSSI, W. SZPANKOWSKI. *On the Entropy of a Hidden Markov Process*, in "TCS", 2007.

- [25] A. LAOUITI, P. MUHLEHALER, Y. TOOR. *Vehicle Ad Hoc NETWORKS (VANETs): Applications and Related Technical Issues*, in "IEEE Communications Surveys and Tutorials", to appear.
- [26] P. MINET, S. MARTIN, L. A. SAIDANE, S. AZZAZ. *FP/FIFO scheduling: coexistence of deterministic and probabilistic QoS guarantees*, in "DMTCS Journal", May 2007.
- [27] P. MINET. *Different approaches to guarantee quality of service (QoS)*, in "Quality of service mechanisms in next generation heterogeneous networks: utopia or reality", A. MELLOUK (editor), Wiley and ISTE/Hermes, to appear.
- [28] P. MINET. *Différentes approches pour la qualité de service (QoS)*, in "Traité IC2, Mécanismes de contrôle de qualité de service: applications temps réel et multimedia", A. MELLOUK (editor), Hermes, Paris, March 2007.
- [29] P. MINET. *Quality of service support in MANETs*, in "Wireless ad hoc and sensor networks", H. LABIOD (editor), Hermes/ISTE, Paris, June 2007, <http://www.amazon.com/Wireless-Ad-Hoc-Sensor-Networks/dp/190520986X>.
- [30] D. NGUYEN, P. MINET. *MANETs with an interference-aware QoS support based on OLSR*, in "IJCIS Journal", to appear.
- [31] D. NGUYEN, P. MINET. *MANETs with an interference-aware QoS support based on OLSR*, in "IJCIS Journal", to appear.
- [32] D. NGUYEN, P. MINET. *Quality of Service Routing in a MANET with OLSR*, in "JUCS, Journal of Universal Computer Science", vol. 13, n^o 1, March 2007, http://www.jucs.org/jucs_13_1/quality_of_service_routing/jucs_13_1_0056_0086_nguyen.html.
- [33] L. SAIDANE, S. B. AYED, P. MINET. *Deterministic and probabilistic QoS guarantees in case of FIFO and EDF local scheduling in a Bluetooth piconet*, in "EURASIP Journal on Wireless Communications and Networking, JWCN", March 2007.

Publications in Conferences and Workshops

- [34] C. ADJIH, E. BACCELLI, P. MINET, P. MUHLEHALER, T. PLESSE. *QoS Support, Security and OSPF Interconnection in a MANET Using OLSR*, in "Military Communications and Information Systems (MCC)", 2007.
- [35] C. ADJIH, S.-Y. CHO, P. JACQUET. *Near Optimal Broadcast with Network Coding in Large Sensor Networks*, in "Workshop on Information Theory for Sensor Networks, WITS 2007", 2007.
- [36] C. ADJIH, P. MINET, P. MUHLEHALER, E. BACCELLI, T. PLESSE. *QoS support, security and OSPF interconnection in a MANET using OLSR*, in "MCC 2007, Military CIS Conference, Bonn, Germany", September 2007.
- [37] C. ADJIH, P. MUHLEHALER, S. BOUDJIT. *DAD-MPR flooding protocol, Convergence Evaluation through Simulation*, in "AINTEC", 2007.
- [38] E. BACCELLI, T. CLAUSEN, P. JACQUET, D. NGUYEN. *Integrating VANETs in the Internet Core with OSPF: the MPR-OSPF Approach*, in "International Conference on ITS Telecommunications (ITST)", 2007.

-
- [39] E. BACCELLI, K. MASE, S. RUFFINO, S. SINGH. *Address Autoconfiguration for MANET: Terminology and Problem Statement*, in "IETF Internet Draft", 2007.
- [40] R. BHASKAR, D. AUGOT, C. ADJIH, P. MUHLETHALER, S. BOUDJIT. *AGDH (Asymmetric Group Diffie Hellman) An Efficient and Dynamic Group Key Agreement Protocol for Ad hoc Networks*, in "NTMS", 2007.
- [41] S. BOUDJIT, C. ADJIH, P. MUHLETHALER, A. LAOUITI. *Autoconfiguration protocol for a multiple interfaces OLSR network*, in "European Wireless", 2007.
- [42] S. BOUDJIT, C. ADJIH, P. MUHLETHALER, A. LAOUITI. *Comparison of flooding techniques for safety applications in VANETs*, in "7th International Conference on Intelligent Transport Systems", 2007.
- [43] L. BOUKHALFA, P. MINET, S. MIDONNET. *A solution for QoS support in wireless ad hoc networks*, in "JDIR 2007, Journées Doctorales en Informatique et Réseaux, Marne-la-Vallée, France", January 2007.
- [44] L. BOUKHALFA, P. MINET, S. MIDONNET. *QoS support in a MANET based on OLSR and CBQ*, in "6th IEEE International Conference on Networking, ICN07, Sainte-Luce, Martinique", April 2007.
- [45] S.-Y. CHO, C. ADJIH, P. JACQUET. *An Association Discovery Protocol for Hybrid Wireless Mesh Networks*, in "Med hoc Net", 2007.
- [46] S.-Y. CHO, C. ADJIH, P. JACQUET. *Heuristics for Network Coding in Wireless Networks*, in "International Wireless Internet Conference", 2007.
- [47] S.-Y. CHO, C. ADJIH, P. JACQUET. *Near Optimal broadcast with network coding in Large sensor networks*, in "International Workshop on Information Theory for Sensor Networks", 2007.
- [48] S.-Y. CHO, C. ADJIH, P. JACQUET. *Rate Selection Heuristics for Network Coding in Wireless Networks*, in "Sigcomm", 2007.
- [49] T. CLAUSEN, C. DEARLOVE. *NEMO Route Optimisation Problem Statement*, in "IETF Internet Draft", 2007.
- [50] T. CLAUSEN, C. DEARLOVE. *Representing multi-value time in MANETs*, in "IETF Internet Draft", 2007.
- [51] T. CLAUSEN, C. DEARLOVE, J. DEAN. *MANET Neighborhood Discovery Protocol (NHDP)*, in "IETF Internet Draft", 2007.
- [52] T. CLAUSEN, J. MACKER, I. CHAKERES. *Mobile ad hoc network architecture*, in "IETF Internet Draft", 2007.
- [53] E. ERWAN, P. MUHLETHALER. *Using OLSR Multipoint Relays (MPRs) to estimate node positions in a Wireless Mesh Network*, in "European Wireless", 2007.
- [54] P. JACQUET. *Common words in two random strings*, in "ISIT", 2007.
- [55] P. JACQUET, B. MANS. *Routing in Intermittently Connected Networks: Age Rumors in Connected Components*, in "PERCOM", 2007.

- [56] P. JACQUET, G. SEROUSSI, W. SZPANKOWSKI. *Noisy Constrained Capacity*, in "ISIT", 2007.
- [57] P. MINET, S. MARTIN, L. A. SAIDANE, S. MASMOUDI. *Probabilistic or deterministic QoS guarantees for flows scheduled with FP/DM*, in "PDCN 2007, IASTED international conference on Parallel and Distributed Computing and Networks, Innsbruck, Austria", February 2007.
- [58] P. MUHLEHALER. *Routage ad hoc multisaut: passage à l'échelle et optimisation du routage*, in "DNAC, Paris", Novembre 2007.
- [59] D. NGUYEN, P. MINET. *Analysis of MPR selection in the OLSR protocol*, in "PAEWN 2007, IEEE international workshop on Performance Analysis and Enhancement of Wireless Networks, Niagara Falls, Canada", May 2007.
- [60] D. NGUYEN, P. MINET. *Scalability of the OLSR protocol with the Fish Eye extension*, in "6th IEEE International Conference on Networking, ICN07, Sainte-Luce, Martinique", April 2007.
- [61] G. RODOLAKIS, C. ADJIH, A. LAOUITI, S. BOUDJIT. *Quality-of-Service Multicast Overlay Spanning Tree Algorithms for Wireless Ad Hoc Networks*, in "AINTEC", 2007.
- [62] L. A. SAIDANE, S. AZZAZ, S. MARTIN, P. MINET. *FP/FIFO scheduling: deterministic versus probabilistic QoS guarantees and p-schedulability*, in "ICC 2007, IEEE International Conference on Communications, Glasgow, Scotland", June 2007.
- [63] A. DE LA FORTELLE, C. LAURGEAU, P. MUHLEHALER, Y. TOOR. *COM2REACT: V2V Communication for cooperative local traffic management*, in "7th International Conference on Intelligent Transport Systems", 2007.

Internal Reports

- [64] C. ADJIH, S.-Y. CHO, P. JACQUET. *Near Optimal Broadcast with Network Coding in Large Homogeneous Wireless Networks*, Technical report, n^o 6188, INRIA, 2007, <http://hal.inria.fr/inria-00145231/fr/>.
- [65] C. ADJIH, S.-Y. CHO, P. JACQUET. *The Performance of Broadcasting with Network Coding in Dense Wireless Networks*, Technical report, n^o 6120, INRIA, 2007, <http://hal.inria.fr/inria-00129782/fr/>.
- [66] E. BACCELLI, T. ZAHN, J. SCHILLER. *DHT-OLSR*, Technical report, n^o 6194, INRIA, 2007, <https://hal.inria.fr/inria-00148347>.
- [67] S.-Y. CHO, C. ADJIH. *Network Coding for Wireless Broadcast: Rate Selection with Dynamic Heuristics*, Technical report, n^o 6349, INRIA, 2007, <http://hal.inria.fr/inria-00186577/fr/>.
- [68] S.-Y. CHO, C. ADJIH, P. JACQUET. *Heuristics for Network Coding in Wireless Networks*, Technical report, n^o 6238, INRIA, 2007, <http://hal.inria.fr/inria-00158082/fr/>.
- [69] T. CLAUSEN. *A MANET architectural model*, Technical report, n^o 6145, INRIA, 2007, <https://hal.inria.fr/inria-00136862>.

-
- [70] P. JACQUET. *Rights and wrongs about wireless network centralized or meshed schemes performance*, Technical report, n^o 6121, INRIA, 2007, <https://hal.inria.fr/inria-00130579>.
- [71] P. JACQUET. *Theoretical results on flooding performance in mobile ad hoc networks*, Technical report, n^o 6122, INRIA, 2007, <https://hal.inria.fr/inria-00130586>.
- [72] S. MAHFOUDH, P. MINET. *A comparative study of energy efficient routing strategies based on OLSR*, Technical report, n^o 6374, INRIA, November 2007, <https://hal.inria.fr/inria-00192899>.
- [73] P. MINET, S. MAHFOUDH. *SERENA: an energy-efficient strategy to schedule nodes activity in wireless ad hoc and sensor networks*, Technical report, n^o 6388, INRIA, December 2007, <https://hal.inria.fr/inria-00196094>.
- [74] L. VIENNOT, P. JACQUET. *Bi-connectivity, k-connectivity and Multipoint Relays*, Technical report, n^o 6169, INRIA, 2007, <http://hal.inria.fr/inria-00142851>.